


BOMFORD

Harrier

- 4.7m or 5.0m reach
- 84 l/min independent hydraulic system
- Semi proportional controls available
- 245° continuous head angling



		4.7	4.7P	5.0	5.0P
A	@ ground level	4.7m 15'5"	4.7m 15'5"	5.0m 16'4"	5.0m 16'4"
B	45° Up bank	4.8m 15'9"	4.8m 15'9"	5.1m 16'8"	5.1m 16'8"
C	45° Down bank	3.0m 9'10"	3.0m 9'10"	3.3m 10'10"	3.3m 10'10"
D	Centre Pivot 1.35m 4'5"	4.0m 13'0"	4.0m 13'0"	4.3m 14'1"	4.3m 14'1"
E	Centre Pivot 1.35m 4'5"	6.0m 19'8"	6.0m 19'8"	6.3m 20'8"	6.3m 20'8"



Features	Description	4.7	4.7P	5.0	5.0P
Tractor Requirements		2100kg	2150kg	2200kg	2250kg
Min hp		50hp	50hp	50hp	50hp
Weight inc Head & Oil		1190kg	1240kg	1240kg	1290kg
Safety Breakaway System	Gravity with hydraulic option	✓	✓	✓	✓
Flail Head	Pro-Trim 1.2metre on 84 litre option	•	•	•	•
Roller Size	100mm (4in), 115mm (4.5in), 150mm (6in)	•	•	•	•
Hydraulic System	Twin Pump 84 l/min = 53hp				
Accessories					
• EPP II Control	Semi Proportional Control	•	•	•	•
• DSR	Rotor reversing valve	•	•	•	•
• Arm Float	Accumulator on first arm	•	•	•	•
• Cutter Bar	1.2m (48in) or 1.5m (60in)	•	•	•	•
• Debris Blower	Blows debris from roadside to reduce punctures	•	•	•	•